



FTX-KN



RX-KM



FTXB-C



RXB50-60C

SPLIT SET FOR WALL SERIES KN/C				TX25KN	TX35KN	TXB50C	TXB60C
Capacity	Refrigeration	(Min.-Nom.-Max.)	W kcal	1.300-2.500-3.000 1.120-2.150-2.580	1.300-3.300-3.800 1.120-2.840-3.270	1.630-5.480-6.200 1.401-4.712-5.332	1.750-6.230-6.500 1.505-5.357-5.590
	Heating	(Min.-Nom.-Max.)	W kcal	1.300-2.800-4.000 1.120-2.410-3.440	1.300-3.500-4.800 1.120-3.010-4.130	1.170-5.620-6.600 1.006-4.833-5.676	1.200-6.400-7.100 1.032-5.504-6.106
Consumption	Refrigeration	Nominal	W	706	1.029	1.710	1.930
	Heating		W	698	943	1.490	1.770
Connections	Liquid		mm	ø 6,4 (1/4")	ø 6,4 (1/4")	ø 6,4 (1/4")	ø 6,4 (1/4")
	Gas		mm	ø 9,5 (3/8")	ø 9,5 (3/8")	ø 12,7 (1/2")	ø 15,9 (5/8")
Power supply				1/220V	1/220V	1/220V	1/220V
No. interconnection wires				3 + T	3 + T	3 + T	3 + T
SEER / SCOP				Cooling / Heating 5,93 / 4,01	Cooling / Heating 6,02 / 4,04	Cooling / Heating 5,93 / 4,27	Cooling / Heating 6,09 / 4,08
Energy efficiency class				Cooling / Heating A+ / A+	Cooling / Heating A+ / A+	Cooling / Heating A+ / A+	Cooling / Heating A+ / A+
Design charge (Pdesign)	Refrigeration		kW	2,50	3,30	5,48	6,23
	Heating (-10°C)		kW	2,40	2,80	3,64	3,80
Seasonal annual energy consumption	Refrigeration		kWh	148	192	331	366
	Heating		kWh	838	978	1.193	1.310

INDOOR UNITS				FTX25KN	FTX35KN	FTXB50C	FTXB60C	
Airflow	Refrigeration		m³/min	10,4	11,8	14,7	16,2	
	Heating		m³/min	11,1	12,8	10,9	17,4	
Fan speed				Nº	5 + A+ S	3 + A	3 + A	
Dimensions	Height		mm	285	285	310	310	
	Width		mm	770	770	1.065	1.065	
	Depth		mm	225	225	224	224	
Weight				Kg	8,5	9,0	14,0	
Sound pressure (A/B/SB)				dBA	40 / 26 / 20	43 / 27 / 20	44 / 38 / 32	46 / 37 / 33
Sound power level				dBA	55	55	55	61

OUTDOOR UNITS				RX25KM	RX35KM	RXB50C	RXB60C	
Compressor type				SWING	SWING	SWING	SWING	
Refrigerant R-410A				kg / TCQeq / PCA	0,70 / 1,5 / 2.087,5	0,94 / 2,09 / 2.087,5	1,45 / 3,02 / 2.087,5	1,45 / 3,02 / 2.087,5
Dimensions	Height		mm	550	550	753	753	
	Width		mm	725	725	855	855	
	Depth		mm	284	284	328	328	
Weight				Kg	24,0	28,0	44,0	44,0
Sound power level				dBA	60	62	64	65
Refrigerant charge for				m	10	10	7,5	7,5
Additional charge				gr/m	20	20	20	20

MODEL		TX25KN	TX35KN	TXB50C	TXB60C
Maximum pipe length (L)	m	15	15	30	30
Maximum level difference (H)	m	12	12	10	10

